


Accessories for Installation

BGJ Series Explosion-proof Connectors



- ◆ Explosion protection to
 - CENELEC
 - IEC
- ◆ Can be used in
 - Zone 1 and Zone 2
 - Zone 21 and Zone 22
- ◆ Available in nickel plated brass, stainless steel or galvanized carbon steel.

Catalogue number logic



Technical data

Explosion-proof connectors

BGJ-□□□(□)/□□(□)

Explosion protection

Global (IECEX)
Gas and dust

IECEX CNEX 18.0038U
Ex db IIC Gb
Ex eb IIC Gb
Ex tb IIIC Db

Europe (ATEX)
Gas and dust

CNEX 18 ATEX 0030U
Ex II 2 G Ex db IIC Gb
Ex II 2 G Ex eb IIC Gb
Ex II 2 D Ex tb IIIC Db

Certificates

Conformity to standards

IECEX; ATEX; CU-TR
EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-31
IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-31

Material

Degree of protection

Ambient temperature

Type

Function




Nickel plated brass, stainless steel or galvanized carbon steel
IP66
-60°C~+100°C
F/F, M/F or M/M
Pipe connector, reducer, connector

Zones 1&2; 21&22

Accessories for Installation

BGJ Series Explosion-proof Connectors

Selection table

Version	Female thread "H"			Dimensions (mm)							Ordering code	Weight (kg)
	Metric	NPT	G	A	B	C	D	L	L1	L2		
 BGJ-I□□(F)/□□(F)	M20	1/2"	1/2"	30	27	25		34	15	15	703001	0.10
	M25	3/4"	3/4"	35	32	31		34	15	15	703002	0.10
	M32	1"	1"	42	38	37		44	19	19	703003	0.15
	M40	1 1/4"	1 1/4"	54	49	46		44	19	19	703004	0.25
	M50	1 1/2"	1 1/2"	60	55	54		44	19	19	703005	0.25
	M63	2"	2"	72	68	67		46	19	19	703006	0.35
	M75	2 1/2"	2 1/2"	88	83	81		46	19	19	703007	0.50
	M90	3"	3"	105	100	98		46	19	19	703008	0.65
	M110	4"	4"	130	125	123		46	19	19	703009	1.00
 BGJ-I□□(M)/□□(F)	M20	1/2"	1/2"	30	27	25	15	36	15	17	703010	0.10
	M25	3/4"	3/4"	35	32	31	18	36	15	17	703011	0.10
	M32	1"	1"	42	38	37	25	44	19	20	703012	0.15
	M40	1 1/4"	1 1/4"	54	49	46	32	44	19	20	703013	0.20
	M50	1 1/2"	1 1/2"	60	55	54	38	44	19	20	703014	0.25
	M63	2"	2"	72	68	67	50	46	19	21	703015	0.35
	M75	2 1/2"	2 1/2"	88	83	81	65	46	19	21	703016	0.50
	M90	3"	3"	105	100	98	75	46	19	21	703017	0.65
	M110	4"	4"	130	125	123	100	46	19	21	703018	1.00
 BGJ-I□□(M)/□□(M)	M20	1/2"	1/2"	30	27		15	36	15	15	703019	0.05
	M25	3/4"	3/4"	35	32		18	36	15	15	703020	0.10
	M32	1"	1"	42	38		25	46	19	19	703021	0.15
	M40	1 1/4"	1 1/4"	50	46		32	46	19	19	703022	0.25
	M50	1 1/2"	1 1/2"	60	55		38	46	19	19	703023	0.25
	M63	2"	2"	72	68		50	46	19	19	703024	0.35
	M75	2 1/2"	2 1/2"	88	83		65	46	19	19	703025	0.50
	M90	3"	3"	100	95		75	46	19	19	703026	0.65
	M110	4"	4"	127	122		100	46	19	19	703027	1.00

Note: 1. Standard material is galvanized carbon steel. Nickel plated brass or stainless steel is optional.

Above weight is based upon galvanized carbon steel.




2. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.



Accessories for Installation

BGJ Series Explosion-proof Connectors

Selection table

Version	Female thread "H1"			Female thread "H2"			Dimensions (mm)	Ordering code	Weight (kg)
	Metric	NPT	G	Metric	NPT	G	L		
 BGJ-II□□(F)/□□(F)	M20	1/2"	1/2"	M25	3/4"	3/4"	36	703028	0.10
	M25	3/4"	3/4"	M32	1"	1"	38	703029	0.15
	M32	1"	1"	M40	1 1/4"	1 1/4"	44	703030	0.25
	M40	1 1/4"	1 1/4"	M50	1 1/2"	1 1/2"	44	703031	0.30
	M50	1 1/2"	1 1/2"	M63	2"	2"	44	703032	0.35
	M63	2"	2"	M75	2 1/2"	2 1/2"	44	703033	0.50
	M75	2 1/2"	2 1/2"	M90	3"	3"	44	703034	0.65
	M90	3"	3"	M110	4"	4"	44	703035	1.00
 BGJ-II□□(M)/□□(F)	M20	1/2"	1/2"	M25	3/4"	3/4"	21	703036	0.05
	M25	3/4"	3/4"	M32	1"	1"	25	703037	0.10
	M32	1"	1"	M40	1 1/4"	1 1/4"	25	703038	0.25
	M40	1 1/4"	1 1/4"	M50	1 1/2"	1 1/2"	25	703039	0.45
	M50	1 1/2"	1 1/2"	M63	2"	2"	25	703040	0.60
	M63	2"	2"	M75	2 1/2"	2 1/2"	25	703041	0.75
	M75	2 1/2"	2 1/2"	M90	3"	3"	25	703042	0.90
	M90	3"	3"	M110	4"	4"	25	703043	1.20
 BGJ-II□□(M)/□□(M)	M20	1/2"	1/2"	M25	3/4"	3/4"	36	703044	0.10
	M25	3/4"	3/4"	M32	1"	1"	40	703045	0.15
	M32	1"	1"	M40	1 1/4"	1 1/4"	46	703046	0.25
	M40	1 1/4"	1 1/4"	M50	1 1/2"	1 1/2"	46	703047	0.25
	M50	1 1/2"	1 1/2"	M63	2"	2"	46	703048	0.35
	M63	2"	2"	M75	2 1/2"	2 1/2"	46	703049	0.50
	M75	2 1/2"	2 1/2"	M90	3"	3"	46	703050	0.65
	M90	3"	3"	M110	4"	4"	46	703051	1.00

Note: 1. Standard material is galvanized carbon steel. Nickel plated brass or stainless steel is optional.




Above weight is based upon galvanized carbon steel.

2. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.

Accessories for Installation

BGJ Series Explosion-proof Connectors

Selection table

Version	Female thread "H"			Dimensions (mm)			Ordering code	Weight (kg)
	Metric	NPT	G	A	B	L		
 BGJ- III□□(F)/□□(F)	M20	1/2"	1/2"	37	15	40	703052	0.15
	M25	3/4"	3/4"	42	20	40	703053	0.25
	M32	1"	1"	48	25	46	703054	0.35
	M40	1 1/4"	1 1/4"	65	32	46	703055	0.50
	M50	1 1/2"	1 1/2"	70	38	46	703056	0.50
	M63	2"	2"	85	50	52	703057	0.85
	M75	2 1/2"	2 1/2"	108	65	52	703058	1.25
	M90	3"	3"	115	76	57	703059	1.70
	M110	4"	4"	145	100	57	703060	2.20
 BGJ- III□□(M)/□□(F)	M20	1/2"	1/2"	37	15	55	703061	0.20
	M25	3/4"	3/4"	42	20	55	703062	0.30
	M32	1"	1"	48	25	64	703063	0.45
	M40	1 1/4"	1 1/4"	65	32	64	703064	0.60
	M50	1 1/2"	1 1/2"	70	38	64	703065	0.65
	M63	2"	2"	85	50	73	703066	1.05
	M75	2 1/2"	2 1/2"	110	102	73	703067	1.45
	M90	3"	3"	115	110	81	703068	1.55
	M110	4"	4"	145	140	81	703069	2.00
 BGJ- III□□(M)/□□(M)	M20	1/2"	1/2"	37	15	64	703070	0.20
	M25	3/4"	3/4"	42	20	64	703071	0.30
	M32	1"	1"	48	25	74	703072	0.45
	M40	1 1/4"	1 1/4"	65	32	74	703073	0.70
	M50	1 1/2"	1 1/2"	70	38	74	703074	0.75
	M63	2"	2"	85	50	84	703075	1.20
	M75	2 1/2"	2 1/2"	110	102	84	703076	1.60
	M90	3"	3"	115	110	94	703077	2.05
	M110	4"	4"	145	140	94	703078	2.55



Note: 1. Standard material is galvanized carbon steel. Nickel plated brass or stainless steel is optional.

Above weight is based upon galvanized carbon steel.

2. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.