


Junction Boxes

BHD51 Series Explosion-proof Junction Boxes



- ◆ Explosion protection to
 - CENELEC
 - IEC
 - NEC
- ◆ Can be used in
 - Zone 1 and Zone 2
 - Zone 21 and Zone 22
 - Class I, Zone 1 and Zone 2
 - Class I, Division 1, Groups A, B, C, D
- ◆ Six types: A, B, C, D, E, F.
- ◆ Type A, B, C, D, E in Copper-free Aluminium Alloy only;
Type F in Copper-free Aluminium Alloy or Cast Iron.

Catalogue number logic



Selection table

Type/Ordering code	Schematic diagram	Weight (kg)	
BHD51-A/M20×1.5	Type A 	0.70	
BHD51-A/M25×1.5			
BHD51-B/M20×1.5	Type B 	0.70	
BHD51-B/M25×1.5			
BHD51-C/M20×1.5	Type C 	0.70	
BHD51-C/M25×1.5			
BHD51-D/M20×1.5	Type D 	0.70	
BHD51-D/M25×1.5			
BHD51-E/M20×1.5	Type E 	0.70	
BHD51-E/M25×1.5			
BHD51-F/M25×1.5	Type F 	Copper-free Aluminium Alloy	0.80
		Cast Iron	2.10

Zones 1&2; 21&22

Junction Boxes

BHD51 Series Explosion-proof Junction Boxes

Technical data

Explosion-proof junction boxes BHD51-□/□/□

Explosion protection

Global (IECEX)

Gas and dust

Europe (ATEX)

Gas and dust

IECEX CQM 11.0022X

Ex db IIC T6 Gb

Ex tb IIIC T80°C Db

CNEX 21 ATEX 0001X

Ex II 2 G Ex db IIC T6 Gb

Ex II 2 D Ex tb IIIC T80°C Db

Certificates

IECEX; ATEX; CU-TR

Conformity to standards

EN 60079-0, EN 60079-1, EN 60079-31

IEC 60079-0, IEC 60079-1, IEC 60079-31

Enclosure material

Copper-free Aluminium Alloy or cast iron, powder coated surface

Enclosure colour

Yellow (RAL1021)

Exposed fastener

Stainless steel

Rated current

≤20A

Rated voltage

Max. 690V AC 50/60Hz, Max. 500V DC

Terminal data

Number

6 terminals (Type A-E), 4 terminals (Type F)

Cross section of cable

0.2~2.5mm²

Degree of protection

IP66

Ambient temperature

-60°C~+60°C

Internal & external earthing

M5

Cable entries

Standard M□×1.5 plug

NPT□ plug on request

Cable gland(optional)

DQM-II (Ex d) or DQM-III (Ex d) is recommended. Please see P6/24~39.

Main application


Type A-E are used for wiring or branching;

Type F is used as accessory for pendant pole type or ceiling type light fittings.


Terminals

Description	Illustration	Number	Ordering code	Weight (kg)	Note
Terminal		6	30008	0.10	For Type A, B, C, D, E
Terminal block		4	30009	0.05	For Type F

Dimension drawings (all dimensions in mm) - subject to alteration




Type A, B, C, D, E




Copper-free Aluminium Alloy

Cast iron



Type F



Application instruction:

1. Type F (Copper-free Aluminium Alloy) is used as mounting accessory for light fittings HRD61-150, BDD81, HRD95 etc.
2. Type F (cast iron) is used as mounting accessory for light fittings HRD61-250, HRD61-400, etc.

