

Selection table						
Version	Rated voltage (V)	Rated current (A)	Rated residual operating current (mA)	Auxiliary contact	Schematic diagram	
BL8060-□/1/□/□/□	230/440/690	1, 2, 4, 6, 10 16, 20, 25, 32 40, 50, 63	/	/		
BL8060-□/1/□/□/ F	230/440/690		/	Indicating contact in OF state		
BL8060-□/2/□/□/□	230/440/690		/	/		
BL8060-□/2/□/□/ F	230/440/690	1, 2, 4, 6, 10 16, 20, 25, 32 40, 50, 63	/	Indicating contact in OF state		
BL8060-□/2/□/□/ L	230/440/690		40	30	/	
				300	/	
		300		/		
		63	30	/		
			300	/		
300	/					
BL8060-□/3/□/□/□	230/440/690	1, 2, 4, 6, 10 16, 20, 25, 32 40, 50, 63	/	/		
BL8060-□/3/□/□/ F	230/440/690		/	Indicating contact in OF state		
BL8060-□/4/□/□/□	230/440/690		/	/		
BL8060-□/4/□/□/ F	230/440/690		/	Indicating contact in OF state		
			/			
Selection table						
Version	Rated voltage (V)	Rated current (A)	Rated residual operating current (mA)	Auxiliary contact	Schematic diagram	
BL8060-d-□/3/□/□/□	230/440/690	63, 80, 100, 125, 160, 250	/	/		
BL8060-d-□/3/□/□/ F	230/440/690		/	Indicating contact in OF state		
BL8060-d-□/3/□/□/ L	230/440/690	63	30	/		
			300			
			300			
BL8060-d-□/4/□/□/□	230/440/690	63, 80, 100, 125, 160, 250	/	/		
BL8060-d-□/4/□/□/ F	230/440/690		/	Indicating contact in OF state		
BL8060-d-□/4/□/□/ L	230/440/690	63	30	/		
			300	/		
			300	/		