

Selection table						
Version	Control motor power (kW)	Rated current of circuit breaker (A)	Adjustable range of setting current of thermal relay (A)	Rated current of contactor (A)	Cable entry size	Enclosure weight (kg)
BLK-160/MS/10	4	10	7~10, Ie=9	12	2 x M25 x 1.5	28.00
BLK-160/MS/16	5.5	16	9~13, Ie=12	18	2 x M25 x 1.5	28.00
BLK-160/MS/20	7.5	20	12~18, Ie=17	25	2 x M25 x 1.5	28.00
BLK-160/MS/32	11	32	16~24, Ie=21	32	2 x M32 x 1.5	28.00
BLK-160/MS/40	15	40	30~40, Ie=32	40	2 x M32 x 1.5	28.00
BLK-160/MS/50	18.5	50	37~50, Ie=40	50	2 x M40 x 1.5	28.00
BLK-160/MS/63	22	63	37~50, Ie=48	65	2 x M40 x 1.5	28.00
BLK-250/MS/10/B	4	10	7~10, Ie=9	12	2 x M25 x 1.5	31.00
BLK-250/MS/16/B	5.5	16	9~13, Ie=12	18	2 x M25 x 1.5	31.00
BLK-250/MS/20/B	7.5	20	12~18, Ie=17	25	2 x M25 x 1.5	31.00
BLK-250/MS/32/B	11	32	16~24, Ie=21	32	2 x M32 x 1.5	31.00
BLK-250/MS/40/B	15	40	30~40, Ie=32	40	2 x M32 x 1.5	31.00
BLK-250/MS/50/B	18.5	50	37~50, Ie=40	50	2 x M40 x 1.5	31.00
BLK-250/MS/63/B	22	63	37~50, Ie=48	65	2 x M40 x 1.5	31.00