

Distribution Boxes

HRMD96 Series Explosion-proof Distribution Panels

Selection table for max. dissipated power

Ta=60℃	HRMD96 with full metal cover without glass		
	T4(T130℃)	T5(T95℃)	T6(T80℃)
Type	Power (W)	Power (W)	Power (W)
HRMD96-I	101	51	22
HRMD96-II	145	73	31
HRMD96-IIB	168	84	41
HRMD96-III	148	74	36
HRMD96-IIIB	188	94	46
HRMD96-IV	190	95	49
HRMD96-IVB	239	119	56
HRMD96-V	279	139	55
HRMD96-VB	299	149	72

Ta=60℃	HRMD96 with metal cover with glass		
	T4(T130℃)	T5(T95℃)	T6(T80℃)
Type	Power (W)	Power (W)	Power (W)
HRMD96-I	101	51	19
HRMD96-II	150	75	30
HRMD96-IIB	155	77	38
HRMD96-III	215	108	38
HRMD96-IIIB	224	112	49
HRMD96-IV	187	93	48
HRMD96-IVB	251	125	53
HRMD96-V	290	145	52
HRMD96-VB	313	157	65



Ta=40℃	HRMD96 with full metal cover without glass		
	T4(T130℃)	T5(T95℃)	T6(T80℃)
Type	Power (W)	Power (W)	Power (W)
HRMD96-I	130	79	43
HRMD96-II	187	114	61
HRMD96-IIB	216	132	89
HRMD96-III	190	116	89
HRMD96-IIIB	242	148	99
HRMD96-IV	244	149	103
HRMD96-IVB	307	188	111
HRMD96-V	358	219	108
HRMD96-VB	384	235	158

Distribution Boxes

HRMD96 Series Explosion-proof Distribution Panels

Ta=40℃	HRMD96 with metal cover with glass		
	T4(T130℃)	T5(T95℃)	T6(T80℃)
Type	Power (W)	Power (W)	Power (W)
HRMD96-I	130	79	38
HRMD96-II	193	118	52
HRMD96-IIB	199	122	65
HRMD96-III	277	169	78
HRMD96-IIIB	288	176	86
HRMD96-IV	240	147	87
HRMD96-IVB	322	197	95
HRMD96-V	373	228	93
HRMD96-VB	403	246	120