

应用场所 Application

- 广泛应用于海洋工程各类作业平台、各类化学品、天然气运输船、危险品码头等危险区域工作及场景照明之用；
- 可在潮湿、振动、腐蚀等恶劣环境中可靠工作；
- 适用于爆炸性危险环境1区、2区、21区、22区等场所。
- Widely used for the illumination on various marine platforms, chemical tankers, LNG ships and hazardous cargo wharfs, etc..
- Can reliably work in severe environment exposed in moisture, vibration or corrosion;
- Explosive hazardous atmosphere Zone 1, Zone 2, Zone 21, Zone 22.



灯体 Housing

- 优质海工铝合金，表面喷塑
- High quality maritime aluminum alloy, powder coated surface

透明罩 Transparent cover

- 钢化玻璃，抗4J冲击
- Toughened glass, stands 4J impact

电气 Electric

- 恒流恒压驱动电源，宽电压输入100V~277V AC 50/60Hz
- Constant current constant voltage drive power, wide voltage input 100V-277V AC 50/60Hz

选配表 Selection table

型号 Type	额定电压(V) Rated voltage	额定功率(W) Rated power	光通量(lm) Luminous flux	防爆标志 Ex-Mark	重量(kg) Weight
HRD92-30	220V/230V 50/60Hz	30W	2480	Ex db IIC T□ ¹⁾ Gb Ex tb IIIC T□ ^{1)c} ¹⁾ 见选配表 ¹⁾ See Selection Table	3.7
HRD92-50		50W	5530		3.7
HRD92-70		70W	7270		5.3
HRD92-100		100W	6820		8.0

- 灯具出厂时配防爆堵头，若用户需要防爆电缆夹紧密封接头，请注明。
- The light fitting is supplied with Ex type stopping plug and Ex cable gland is on request.

防爆标志选配表 Ex-Mark Selection table




额定功率(W) Rated power	温度组别 Temperature classification			
	-40℃≤Ta≤+40℃		-40℃≤Ta≤+55℃	
	气体 Gas	粉尘 Dust	气体 Gas	粉尘 Dust
30, 50, 70, 100	T6	80℃	T5	95℃

技术参数 Technical parameters

执行标准 Conformity to standards	IEC 60079, EN 60079, GB/T 3836, CCS 入级规范 (CCS standard)
环境温度 Ambient temperature	-40°C~+40°C, -40°C~+55°C(可选 Optional)
光源类型 Light source	LED 模组 LED module
色温 Color temperature	5700K ± 250K
显色指数 Color rendering index	Ra ≥ 70
防护等级 Degree of protection	IP66
防腐等级 Corrosion-proof	WF2
电缆引入口 Cable entris	4 × M25 × 1.5堵头(铝合金), 推荐配2 × M25 × 1.5格兰(黄铜镀镍) DQM-II/III Ex db, 适用于Φ 12.5~Φ 20.5mm电缆 4×M25×1.5 plug (Aluminum alloy). 2×M25×1.5 gland (Nickel plated brass) DQM-II/III Ex db is recommended, suitable for Φ 12.5~Φ 20.5mm cable
接线端子 Terminal	1.5~4mm ²




外形尺寸 Outline dimension

cd/1000lm






30W、50W

cd/1000lm



70W

cd/1000lm



100W

配光曲线
Light distribution curve